VC70 SD & HD

The portable control panel facilitates the operation of Verisight Ultra and AGILIOS. The multifunctional panel can transmit images, videos, and WinCan projects. With an IP54 housing that can be opened and closed, it protects the tablet and enables indoor and outdoor use. For more convenient use, it can be connected to other Bluetooth devices.



1080p FULLHD DS_05-07-2024_VC70_EN_Rev_1

TECHNICAL DATA VC70 SD & HD

Display type 10.9-inch (277mm Diagonale)

LED backlit Multi-Touch Display mit IPS technology

Display format Portrait (16:10)

Display resolution 2360px x 1640px

Display brightness 500 nits Brightness

Interfaces 1 * USB (Data Export)

1 * USB-C (Charging)

1 * WLAN

Wireless standard Wi-Fi 6 (802.11ax)

Internal memory 128 GB

Video storage capacity max. 30 Hours. FullHD (60MB/Min)

max. 85 Hours SD (23MB/Min)

Video resolution HD (1280x720 px)

Video format/picture format MPEG4 (H.264)/JPEG oder PNG

(selectable)

Power supply USB-C

Protection class IP54, open and closed

Ambient temperature range 0°C to 35°C

Storage temperature range -20°C to 45°C

Material PVC (ABS & PC)

Dimensions (WxHxD) 390 x 309 x 112

Weight Approx. 4 kg

ADVANTAGES AT A GLANCE

VC70 SD & HD

- Control unit for all iPEK push systems: AGILIOS SD, HD and Verisight Ultra
- · Operation, control, and image transmission via Wi-Fi
- Operation via keyboard and touch possible even with gloves
- Real-time image transmission via Wi-Fi to a daylight-suitable touch screen with high resolution
- · Video streaming to another local device
- Battery life approx. 3 hours, charging via USB-C port while closed
- Robust housing with IP54, both open and closed
- Ergonomic
- QWERTZ silicone keyboard with shortcut keys for frequently used functions and position keys for control
- Date exchange for saving images, videos, and reports via USB connection

VISIONREPORT APP

Features

Zoom, focus, light control, image capturing, and video recording without having to create a project, browse thumbnail galleries, data and text input, seamlessly export observation data to WinCan software/cloud, send emails directly to customers, probe frequency, counter, etc.

COMPATIBLE WITH:

- · Verisight Ultra
- · AGILIOS HD
- AGILIOS SD
- PTP50SD+HD
- AC40SD+HD

NOT COMPATIBLE WITH:

- ROVION
- DCX5000
- VC500



Subjects to changes www.ipek.at